

Image Sensor

powered by  **ALARM.COM**



OVERVIEW

The Interlogix Image Sensor represents an innovative advancement that combines a Passive Infrared (PIR) motion sensor, an integrated still camera, wireless communication and Alarm.com Interactive Services. Designed to deliver better security through visual verification of alarms, this sensor helps increase engagement through on-demand property views.

ETL certified and battery operated, the Image Sensor communicates with Interlogix security control panels and can be swapped for standard motion sensors for increased end user value and higher RMR. Integrated with Alarm.com's Interactive Services, images are easily accessible. All uploaded images are viewable on the Alarm.com Customer Web site or through mobile apps for added convenience. Users can even receive images via text or email alerts whenever an image is uploaded—either from an alarm event or if requested on-demand.

Compatible with Simon XT[®], Simon XT_i, and Concord 4 panels, the Image Sensor requires an Alarm.com module with an attached Image Sensor daughterboard (refer to System Compatibility under specifications for panel specific firmware requirements).

STANDARD FEATURES

- ETL certified for UL 639
- 35' x 40' detection coverage area
- Remotely configurable PIR sensitivity, such as Pet Immunity
- Easy installation, no broadband or router configuration
- Tamper detection and walk test mode
- Color images
- Night vision, IR illumination
- Wireless image transmission to Alarm.com via cellular networks



How It Works

